

Product Data Sheet

Castrol EDGE 10W-60

Boosted with TITANIUM FST™ - Strength for Maximum Performance

Description

Advances in engine technology have led to increased power and efficiency, meaning engines work harder and under higher pressures than ever before. The only thing keeping metal engine components apart is the oil, so it needs to be strong and remain strong.

Castrol EDGE is our strongest and most advanced range of engine oils. Its *TITANIUM FST*TM doubles its film strength, preventing oil film breakdown and reducing friction.

Castrol EDGE boosted with *TITANIUM FST™*: helping your engine perform at its best.

Application

Castrol EDGE 10W-60 is suitable for use in Supercars where the manufacturer recommends an ACEA A3/B4 10W-60 lubricant, including: Aston Martin V8 Vantage S, Ferrari F12 Berlinetta, Ferrari FF. Please refer to your owners handbook.

Castrol EDGE 10W-60 is approved for use in Supercars where the manufacturer requires a VW 501 01/505 00 approved product, including: Audi R8 V10 GT, Bugatti Chiron, Bugatti Veyron. Please refer to your owners handbook.

Castrol EDGE 10W-60 is approved for BMW M-Models.

When choosing oil, please refer to your owner's handbook and the product specifications shown below. May also be suitable for other vehicles.

Advantages

Castrol EDGE 10W-60:

- Maximises short and long term engine performance
- Delivers outstanding levels of protection across a variety of driving conditions and temperatures
- Reduces engine deposits to help maximise engine response*
- Proven and tested in world leading supercars

^{*} Compared to the limit in the ASTM D 6593 Seq VG test

Typical Characteristics

Name	Method	Units	Castrol EDGE 10W-60
Density @ 15C, Relative	ASTM D4052	g/ml	0.853
Viscosity, Kinematic 100C	ASTM D445	mm²/s	22.7
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	4879
Viscosity, Kinematic 40C	ASTM D445	mm²/s	160
Viscosity Index	ASTM D2270	None	173
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	203
Ash, Sulphated	ASTM D874	% wt	1.29

Product Performance Claims

ACEA A3/B3, A3/B4 API SN/CF Approved for BMW M-Models VW 501 01/ 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE 10W-60
08 Jan 2018
Control the Control logo and related may

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.